

Glow67 Pro Series

24VDC IP67 Dot-less High-Power LED Tape



Features

- Spec-grade for wet location installs
- Dot-free for smooth lighting
- 703 lumens per foot
- 90+ CRI for true color
- Plug-and-play connectors made for Glow67
- Slim, flexible, easy to install
- Cuttable every 1.04 inches
- Works with all dimming protocols
- 6-year warranty, UL/CE listed

Accessories (Included only with the 16ft tape)

Ordering Code

Glow67-TC-KIT

Description

1. Glow67-TT - 1pc
2. Glow67-TW - 1pc
3. Glow67-EC - 1pc
4. Glow67-WC - 1pc
5. Glow67-SS - 1 pc



Specifications

Input voltage:	24VDC
CRI:	90
Power:	5.8W/ft
Lumens:	703lm/ft
Cut Length:	1.04" (26.3mm)
Environment:	IP67
Dimensions (W x H):	0.47" x 0.18" (12 x 5.2mm)
Beam Angle:	150°
Maximum run:	25ft (145 Watts)
Lamp Life:	50,000 Hours
Operating Temp:	-4°F to 113°F (-20°C to 45°C)
Adhesive:	3M
Warranty:	5 years
Dimming Control:	Incandescent • CFL/LED • MLV ELV • 0-10V • Dimmer switch / wireless app & wall switch.

Connectors and Wire

Ordering Code

Glow67-TT	0.47" (12mm) Tape to tape connector
Glow67-TW	0.47" (12mm) Tape to wire connector with a 11.8" lead wire
Glow67-EC	0.47" (12mm) End cap
Glow67-WC	0.47" (12mm) Wall Clip and Two Screws
Glow67-SS	Wet Location Silicone Sealant
WS-2P-15	15ft 2 Pin 15ft Wire Spool
WS-2P-250	250ft 2 Pin 250ft Wire Spool

Ordering Code Length

Glow67-27-16	16.4 ft.
Glow67-27-164	164ft.

Mechanical Diagrams

